




FIREPLACE FOR LARGE SPACES

Heat Output Cord Wood 99,000 BTU

38,500 BTU EPA Test Fuel


Efficiency (LHV)	76.8%
Emissions	2.47 gm/hr.
Log Size (max)	18–20 inches
FIREBOX SIZE	3.0 cu.ft.
Glass Size	246 sq.in.
Weight	626 lb.

Heat larger spaces with the reduced footprint of a wallmount fireplace: the FP30 offers the best of traditional wood heat, with a contemporary look and all the Pacific Energy extras. Handcrafted with a floating firebox of heavy gauge steel, a high capacity baffle system, and EBT2 extended heat technology, this full-featured unit is designed for a lifetime of efficient, effective heating. And with clean, uncluttered lines and a huge viewing window (that remains clear with Airwash technology) it meets the highest expectations for form and function.



EAT DISTRIBUTION

POWERED HEAT DISTRIBUTION SYSTEM Above or below grade 5 to 20 feet





STANDARD FEATURES

EPA Certified

Reliable, durable non-catalytic technology Air wash system for super clean ceramic glass Boost air for easy lighting Oversize glass viewing window Floating firebox for extended stove life 304 Stainless Steel Baffle, insulation cover, rails and flame shield High-tech multi-port combustion air injection system Extended Burn Technology (EBT2) Easy and safe front to back fuel loading 3 cubic foot Summit firebox 125 cfm temperature actuated blower Single-Lever Air Control Cast iron door with ash lip Cast Iron grills Mobile Home Approved Requires 6" chimney

PERFORMANCE OPTIONS EPA Certified Powered Heat Distribution System Image: ALR WASH Image: ALR WASH Image: BAFFLE SYSTEM Image: BAFFLE SYSTEM

WWW.PACIFICENERGY.NET