

CAPRI 34/44

DIRECT VENT GAS FIREPLACE INSERT FLUSH MOUNT SERIES



INSERT

YOUR STYLE HERE

The **CAPRI** Insert is a wonder, able to transform an existing wood burning fireplace into an updated focal point in any room. This Flush Mount Series is available in two sizes and your choice of liner, driftwood, oak or birch log set, decorative stone, or five different colors of crushed glass media.

With so many options, you'll find the **CAPRI** is perfectly attuned to your décor vision.

Visit marquisfireplaces.net to see the latest evolution in fireplaces.

CAPRI

STANDARD FEATURES

- Dual Burner with glowing embers and decorative ash bed
- Millivolt or IPI (Intermittent Pilot Ignition)
 valve system allows operation during
 power failure with adjustable flame control
- Heat activated blower with variable speed control
- · Heat radiating Ceramic Glass
- · On/Off Rocker switch
- Proflame II Models include Remote Control; features flame, fan, thermostat, and smart thermostat (IDV34NE2, IDV34LPE2, IDV44NE2, IDV44LPE2 Models only)
- · Safety Screen Barrier



OPTIONAL FEATURES

Designer Doors and Frames:Black; Picture Frame or Series 1 Designer Door

Surrounds:

Black; Picture Frame or Universal

Liners:

Traditional Brick, Herringbone Brick, Porcelain Reflective or Fluted

Media Options:

Decorative Stones, Ember Chunks, Decorative Ember Glass (Glacier Ice, Cobalt Blue, Black, Bronze, White), Natural Rocks, or Multi-Colored Rocks

Log Sets:

Choice of Two Split Oak Sets, Two Driftwood Sets, or a Birch Log Set

Thermostats:

Standard On/Off or Programmable (wall mount)









CAPRI VARIATIONS

CLEAN VIEW CV3 WITH DOOR FRAME



CLEAN VIEW CV6 WITH BACKER SURROUND





CAPRI PRODUCT SPECIFICATIONS

Fuel
Gas Control
Input Max.
Input Min.
Glass Size
FE (P.4.1-15)
Venting

IDV34N IDV34LP IDV34NE2 IDV34LPE2 Natural Gas Propane Millivolt / IPI Millivolt / IPI 31,000 BTU 28,500 BTU 20,900 BTU 23,100 BTU 25 5/8"W x 14 1/8"H 25 %"W x 14 1/8"H 62.86% / 64.73% 63.63% / 68.30% 3"/3" 3"/3"

IDV44NE2
Natural Gas
Millivolt / IPI
34,250 BTU
24,000 BTU
29 1/8" W x 18 3/8" H
60.18% / 61.70%
4" / 3"

IDV44N

IDV44LPE2
Propane
Millivolt / IPI
30,000 BTU
22,840 BTU
29 1/8" W x 18 3/8" H
60.20% / 61.85%
4" / 3"

IDV44LP

CLEAN VIEW CV1 WITH DOOR FRAME & SURROUND

CLEAN VIEW CV2 WITH SURROUND

CLEAN VIEW CV4 WITH PICTURE FRAME







Unit Illustrated: IDV34N Direct Vent Insert (Natural Gas), MQ34CV3BL Clean View (Black), MQ34DD1BL Designer Door (Black), I34S3927BL Surround (Black), MQRBRW Birch Log Set, MQRSP11 Log Support Platform, MQ65C Glass Media Bronze x3, IDV33PRL Porcelain Liner.

Unit Illustrated: IDV34N Direct Vent Fireplace Insert (Natural Gas), I34CV1BL Clean View (Black), MQRSP8 Glass Support Platform, MQSTONE Decorative Stones.

Unit Illustrated: IDV44N Direct Vent Fireplace Insert (Natural Gas), MQ44CV2BL Clean View (Black), LOGF36 Log Set (Fibre Split Oak), I44S4432BL Surround (Black), IDV36RLT Refractory Brick Liner (Traditional).

Unit Illustrated: IDV34N Direct Vent Insert (Natural Gas), MQ34CV4PFBL Clean View – Picture Frame (Black), MQ34SF1BL Door Frame (Black), MQRSP8 Glass Support Platform, MQG5A Decorative Ember Glass (Cobalt Blue), IDV33PRL Porcelain Reflective Liner.

IDV34 IDV44

CLEAN VIEW KITS (REQUIRED) AND SURROUNDS (IF NEEDED)

Minimum Fireplace Openin	g wiath	Height	Deptn
IDV34 with: I34CV1 / MQ34CV2	/ MQ34CV3 /	MQ34CV4F	PF
	28 5/8"	21 1/2"	17 3/4"
IDV34 with: I34CV6BL	26 1/4"	21 3/8"	14 ³ / ₈ "
Clean View Kits	Width	Height	Depth
I34CV1BL (Clean View)	35 1/4"	24 3/16"	¹³ / ₁₆ "
I34CV6BL (Clean View)	37 %"	26 15/16"	2 3/4"
10 10 10 1 (o.ca.: 1.c.:.)			

Minimum Firence Opening Width Height Donth

IDV44	32 1/8"	25 ¾"	18"
Clean View Kits	Width	Height	Depth
I44CV1BL (Clean View) MQ44CV2BL (Clean View)	39 %16" 39 5/8"	28 ½" 29 ½6"	¹³ / ₁₆ " 1 ³ / ₄ "

Clean View Kit – with Screen Door or Designer Frame

Width

41 1/16"

Width Height Depth

Height Depth

1 1/16"

29 1/8"

Minimum Fireplace Opening

Clean View Kit – with Screen Door or Designer Frame			
	Width	Height	Depth
MQ34CV3BL (Clean View)*	37 1/8"	25 3/16"	1 7/16"
MQ34DD1BL (Designer Door – Series 1)			
MQ34SF1BL (Door Frame)			
*NOTE: When using an MQ34CV3BL a Designer Door or Door Frame is required.			

	MQ44SF1BL (Door Frame)
quired.	*NOTE: When using an $\mathbf{MQ44CV3BL}$ a Designer Door or Door Frame is required.

MQ44CV3BL (Clean View)*

MQ44DD1BL (Designer Door - Series 1)

Clean View Picture Frame	Width	Height	Depth
MQ34CV4PFBL (Clean View)*	37 1/8"	27 3/8"	1 7/16"
MQ34DD1BL (Designer Door – Series 1)			
MQ34SF1BL (Door Frame)			

*NOTE: When using an MQ34CV4PFBL a Designer Door or Door Frame is required.

Surrounds	Width	Height
I34S3927BL (Surround)	39"	27 5/16"
I34SPF4131BL (Surround Picture Frame)	41 1/8"	31 %"
I34SU4541BL (Surround Universal)*	45"	41"
*Trim to Size		

Surrounds	Width	Height	
I44S4432BL (Surround)	44"	32 1/16"	
I44SPF4436BL (Surround Picture Frame)	44"	36"	
I44SU4742BL (Surround Universal)*	47"	42"	
*Trim to Size			

VENTING

IDVVT36 IDVFK25	Vertical Vent Termination Flex Pipe Kit
IDVLCP	Block Off Plate – for Lower Chase
ZDV3FC	Flex Connector 3" Diameter
*MC D /O	- K:+ #4CDVA_CL22V

*MG Duravent (Order Kit #46DVA-CL33)


IDVVT43	Vertical Vent Termination
143FK25	Flex Pipe Kit


I43LCP Block Off Plate – for Lower Chase
ZDV3FC Flex Connector 3" Diameter
ZDV4FC Flex Connector 4" Diameter

*MG Duravent (Order Kit #46DVA-CL34)

DIMENSIONS


FRONT VIEW





TOP VIEW

SIDE VIEW



IDV34	IDV44
28 %"	32 %"
14 1/8"	18 3/8"
25 %"	29 %"
3"	4"
3"	3"
21 3/8"	25 ¾"
18 ¼"	18 %16"
28 %16"	32 %"
21 1/4"	25 ¾"
18 ¼"	18 %16"
	28 5/8" 14 1/8" 25 5/8" 3" 3" 21 3/8" 18 1/4" 28 9/16" 21 1/4"




Unit Illustrated: IDV34N Direct Vent Insert (Natural Gas), MQ34CV4PFBL Clean View (Picture Frame – Black), MQ34SF1BL Door Frame (Black), MQL0GF33 Driftwood Log Set, MQRSP11 Support Platform for Driftwood, IDV33PRL Porcelain Reflective Liner.

CAPRI ACCESSORIES


DESIGNER DOORS & FRAMES

REQUIRED FOR MQ34CV3, MQ34CV4PF AND MQ44CV3

LOG SETS




MQLOGF34 Fiber Split Oak (for IDV34/44)




LOGF35 Fiber Split Oak (for IDV34)



LOGF36 Fiber Split Oak (for IDV44)



MQLOGF33 MQLOGF453 Driftwood (MQRSP11 required)



MQRBD4 Driftwood (MQRSP11 and 15 lbs Glass Media required)



MQRBRW Birch (MQRSP11 and 15 lbs Glass Media required)



Designer Frame



Designer Door

MEDIA OPTIONS

REQUIRES GLASS SUPPORT PLATFORM (MQRSP8) OR ROCK SUPPORT PLATFORM (MQRSP4)



MQG5ZG Zircon Glacier Ice Glass



MQG5A Cobalt Ember Glass




MQG5B Black Ember Glass



MQG5C Bronze Ember Glass



MQG5W White Ember Glass



MQROCK3 Multi-Colored Rock Set

LINERS



IDV33RL IDV36RLT Traditional Brick



IDV36RLH Herringbone Brick (IDV44 only)



MQEMBER Ember Chunks




MQSTONE Decorative Stones



MQSTONE10 Decorative Stones



MQROCK2 Natural Rock Set



MQ33RLF MQ43RLF Fluted



IDV33PRL IDV36PRL Porcelain Reflective





Marquis Fireplaces maintains a program of continuous testing, refinement and improvements of all its products. Some aspect of units shown here may be changed at any time without notice or obligation.

Certification: These Models are certified to ANSI Z21.88-2017 CSA 2.33-2017 Vented Gas Fireplace Heaters.

Note: Components may have to be ordered separately to create a complete unit. Discuss with your local Marquis Dealer for clarification.

Canadä

ENER GUIDE

Look for the **EnerGuide** Gas Fireplace Energy Efficiency Rating in this brochure

Based on CSA P.4.1-15



FOR CALIFORNIA RESIDENTS ONLY:

to chemicals including Carbon Monoxide, that is an externally vented by-product of fuel consumption, which is [are] known to the State of California to cause birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov.

Crafted entirely in Canada, each Marquis fireplace is built to the highest standards and made to last.

LIMITED LIFETIME WARRANTY



2340 Logan Avenue Winnipeg, Manitoba, CAN R2R 2V3 Phone: 204.632.1962 Fax: 204.632.1960 marquisfireplaces.net

Printed in Canada B105 - 02/2020