

SOLACE zero clearance direct vent gas fireplace

Unit Illustrated: Solace HBZDV4736N Direct Vent Fireplace, LOGF36 Fiber Split Oak Log Set, VLBIT4 Log Bits, HB47CVCK Designer Clean View Circulating Kit, HB47RRH Red Herringbone Brick Liner.



SOLACE SPECIFICATIONS

	Model	MQHBZDV3636N/NE MQHBZDV4236N/NE	MQHBZDV3636LP/LPE MQHBZDV4236LP/LPE	HBZDV4736N HBZDV4736NE	HBZDV4736LP HBZDV4736LPE
SOLACE	Flue	Top	Top	Top	Top
	Fuel	Natural Gas	Propane	Natural Gas	Propane
	Input Max.	30,500 BTU	29,000 BTU	40,000 BTU	36,000 BTU
	Input Min.	29,000 BTU	22,200 BTU	27,000 BTU	30,000 BTU
	FE (P.4.1-15)	61.98% / 63.92%	67.63% / 69.25%	60.39% / 61.88%	53.79% / 54.90%
	Log Set	LOGF36	LOGF36	LOGF36	LOGF36
	Model	HBZDV3624N/NE	HBZDV3624LP/LPE	HBZDV4224N/NE	HBZDV4224LP/LPE
=	Flue	Тор	Тор	Тор	Тор
CE	Flue	Top	Top	Top	Top
	Fuel	Natural Gas	Propane	Natural Gas	Propane
CE I	Flue	Top	Top	Top	Top
	Fuel	Natural Gas	Propane	Natural Gas	Propane
	Input Max.	24,00 BTU	22,000 BTU	24,000 BTU	22,000 BTU
Ξ.	Flue	Top	Top	Top	Top
	Fuel	Natural Gas	Propane	Natural Gas	Propane

TOP FLUE	Height		Front	Width	Depth		
MODEL	Actual	Framing	Actual	Framing	Actual	Framing	
LOUVERS							
HBZDV36	34 ¹³ /16"	35"	36"	36 3⁄8"	16 7⁄16"	17"	
HBZDV42	37"	37 ¾"	41 1/8"	42 ¾"	16 7⁄16"	17"	
HBZDV47	43 1⁄16"	43 1⁄8"	47 ¼16"	47 ³ /8"	19 7⁄16"	19 ½"	
CLEAN VIEW	CIRCULATI	NG KIT					
HBZDV36	34 11/16"	41"	38 1⁄16"	38 7⁄16"	18 1⁄8"	19 ½"	
HBZDV42	36 ¹³ ⁄16"	43"	42 1⁄16"	42 1/16"	18 ¹⁵ /16"	19 ½"	
HBZDV47	49"	49 ½"	48 1/16"	48 ¾"	21 ¹⁵ /16"	22"	

A 58¹³/16"

B 42 ³/₈"

C 41 ⁷/₈"

D 8 1/4"

E 41 5/8"

F 13 ³/₄"

G 19 ½"

H 29 7/16"

A 54 ¹³/₁₆"

B 36 3/8"

C 36"

D 9 ³/₁₆"

E 38 ³/₄"

F 12 ⅔"

G 17 %16"

H 27 3/8"

TOP FLUE MODEL VIEWING AREA

Height

18 5⁄8"

20 3/8"

26 3/8"


marq uis

Width

HBZDV36 29 3/4"

HBZDV42 33 3/8"

HBZDV47 39 1/2"



CORNER FRAMING DIMENSIONS (INCHES): LOUVERED UNITS				MING DIMENS	IONS (INCHES): KIT (CVK)
HBZDV36	HBZDV42	HBZDV47	HBZDV36	HBZDV42	HBZDV47

HE	SZDV47	HB	ZDV36	HE	ZDV42	HB	ZDV47
A	65 ¼"	Α	59 ⁷ / ₈ "	A	63 ¹³ /16"	A	70 ³ /16"
В	47 ³ /8"	В	38 7⁄16"	В	42 1/16"	В	48 ¾"
С	47 ¼ ₁₆ "	С	38 1⁄6"	С	42 1⁄16"	С	48 1⁄16"
D	8 ¹⁵ / ₁₆ "	D	10 11/16"	D	10 11/16"	D	10 %"
Ε	46 1⁄8"	Ε	42 5/16"	Ε	45 ½"	Е	49 ⁵ /8"
F	13 ¹⁵ /16"	F	12 3⁄8"	F	13 ¾"	F	13 ¹⁵ /16"
G	19 ¹¹ / ₁₆ "	G	17 %16"	G	19 ½"	G	19 ¹¹ /16"
Н	32 5⁄8"	Н	29 5/16"	Н	31 %"	Н	35 1⁄16"



Unit Illustrated: Solace II HBZDV4224N Direct Vent Fireplace, MQLOGC45 Oak Log Set, HB42GBL Grill Kit (Black), HB42RLT Traditional Brick Liner.



Unit Illustrated: Solace II HBZDV3624N Direct Vent Fireplace MQLOGC45 Oak Log Set, HB36CVCK Designer Clean View Circulating Kit, HB36RLH Herringbone Brick Liner.

SOLACE

SOLACE ACCESSORIES

Imagine lively gatherings or times of quiet reflection in front of the beautiful Solace II. Available in two sizes, the Solace II allows you to transform your fireplace into something truly unique.

With so much style and attention to detail, the Solace II is available in a range of sizes and styles. You can choose from our mid-efficient rated fireplace for ambiance and taking the chill out of the room, or our higher-efficient version for additional warmth.

Visit www.marquisfireplaces.net to see the latest evolution in fireplaces.

STANDARD FEATURES

- Millivolt or IPI valve system allows operation during a power failure with Hi/Low heat and flame adjustment
- Dual burner with Realistic Flame Pattern
- Safety Screen Barrier

OPTIONAL FEATURES

Designer Clean View Circulating Kit: No Louvers Required

Louvers: Grills available in Black

Fan Kit: Heat activated with variable speed control

Accessories: Log sets or rock sets required

Liners: Porcelain Reflective Liner or Brick Liners

LOG SETS





LOGF36 Fibre Split Oak (SOLACE)





LOGC42 (SOLACE II)

ROCK SETS

REQUIRES SUPPORT PLATFORM (SOLACE | ONLY)



MQROCK2 Natural Rock Set



MQROCK3 Multi-Colored Rock Set







LINERS



REMOTE CONTROLS

GFRC. F1 OR MV



RRH **Red Herringbone Brick**

THERMOSTATS

Wall Mount or Programmable





Traditional Brick

FY BB







Marquis Fireplaces maintains a program of continuous testing, refinement and improvements of all its products. Some aspect of units shown here may be changed at any time without notice or obligation.

Certified to: ANSI Z21.88-2017 • CSA 2.33-2017 Vented Gas Fireplace Heaters, CSA 2.17-2017 Note: Components may have to be ordered separately to create a complete unit. Discuss with your local Marquis Dealer for clarification.

Canadä

ENERGUIDE

Look for the **EnerGuide** Gas Fireplace Energy Efficiency Rating in this brochure

FOR CALIFORNIA RESIDENTS ONLY:

WARNING! This product can expose you to chemicals including Carbon Monoxide, that is an externally vented by-product of fuel consumption, which is [are] known to the State of California to cause birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov. Crafted entirely in Canada, each Marquis fireplace is built to the highest standards and made to last.

LIMITED LIFETIME WARRANTY



2340 Logan Avenue Winnipeg, Manitoba, CAN R2R 2V3 Phone: 204.632.1962 Fax: 204.632.1960 marquisfireplaces.net

Printed in Canada **B057 – 03/2020**