



E25

GAS FIREPLACE INSERT



enviro.com

E25

GAS FIREPLACE INSERT




Insert Specifications

BTU Maximum Input - NG	28,000 BTU
BTU Minimum Output*	14,000 BTU
Heating Area	1,600 ft ²
P4 Efficiency	TBA
Glass Size	420 in ²
Minimum Install Dims.	HEIGHT: 19 ⁷ / ₈ " WIDTH: 27 ⁷ / ₈ " DEPTH: 13 ³ / ₄ "

* Turn down is based on a 50% valve.

Clearance to Combustibles

Mantle pillar to the edge the of glass	21"
Min. non-combustible surface in front of unit	16"
Floor to an 8" wide mantle	36"



Design Features

- SIT Valve 820 (Standing Pilot)
- SIT Valve 885 (IPI System with Remote)
- Glass Size: 26¹/₄" x 16", 420 in²
- Included Traditional Log Set
- Easy Access Burner Switch (NOVA)
- Stainless Steel Burner
- Steel Firebox Grate
- Enviro's Smallest Install Depth - Only 13³/₄"
- Limited Lifetime Warranty

Gas Insert Options

- Hearth Riser
- Traditional Log Set - Included
- Liner Options:
 - Painted Liner - Included
 - Brick Liner
- Surround Options:
 - Surround Panel - Included 25³/₄" x 39"
 - Trimmable Panel 30.2" x 48"
- Optional 110 CFM Fan - Included with IPI



Manufactured by Sherwood Industries Ltd • Victoria, BC, Canada
enviro.com • info@enviro.com • Printed in Canada, May 2020

Designed & Built in
North America